



RCMT / RCGT

Designation	S	D1	IC
	mm	mm	mm
RCGT 0602..	2,38	2,8	6
RCGT 0803..	3,18	3,4	8
RC.T 1003..	3,18	4,0	10
RCMT 1204..	4,76	4,9	12
RCMT 1606..	6,35	5,3	16
RCMT 2006..	6,35	6,5	20
RCMT 2507..	7,94	7,2	25



RCMT / RCGT




ISO	RE mm	F	M	M	M	M	M	M
		RCMT 1A/08	RCGT 1A/08	RCGT 1A/08	RCMT 1A/08	RCMT 1A/08	RCMT 1A/08	RCGT 1A/90
0602MOEN	3,0							
0602MOFN	3,0							6,03 600
0803MOEN	4,0							
0803MOFN	4,0							6,73 602
1003MOFN	5,0							
1003MOSN	5,0							6,73 604
1204MOSN	6,0							
1606MOEN	8,0	18,13	038					
1606MOSN	8,0							
2006MOSN	10,0							
2507MOSN	12,5							

9

RCGT

-27 CWN15	-27 AMZ
-AL CWN15	-AL AMZ



M
RCGT
1A

M
RCGT
1A/90


Article no. 70 266 ...	Article no. 70 266 ...
EUR 8,03	EUR 7,87

300
302
502

ISO	RE	mm	Article no.	Article no.
0602MOFN	3		70 266 ...	70 266 ...
0803MOFN	4		8,03	7,87
Steel			300	502
Stainless steel				○
Cast iron				○
Non ferrous metals			●	●
Heat resistant alloys				

RCGT

Designation	S	D1	IC
	mm	mm	mm
RCGT 0602..	2,38	2,8	6
RCGT 10T3..	3,97	4,4	10



RCGT-F


RCGT

-F-CB1 CTDPD20	-F-CB1 CTDPS30	-F-CB2 CTDPS30
-CB1 PDC	-CB1 PDC-S	-CB2 PDC-S
F DIAMOND RCGT	F DIAMOND RCGT	M DIAMOND RCGT
Y0 Article no. 71 315 ... EUR	Y0 Article no. 71 315 ... EUR	NEW Y0 Article no. 71 316 ... EUR

ISO	RE	LE				
	mm	mm				
0602M0EN	3	6				
0602M0FN	3	6	146,20	102	146,20	202
10T3M0EN	5	10				
10T3M0FN	5	10	191,80	104	191,80	204

Steel	●	●	●
Stainless steel			
Cast iron			
Non ferrous metals	●	●	●
Heat resistant alloys	○	○	○

MaxiLock-S - SRDC 0° - Toolholder with screw clamping

Neutral
2A/24Article no.
70 708 ...
EUR

ISO designation	H	B	OAL	LH	WF	Insert	torque moment Nm	
	mm	mm	mm	mm	mm			
SRDC N 1212 F06	12	12	80	12,4	9,0	RC.. 0602 MO		73,60
SRDC N 1616 H06	16	16	100	12,4	11,0	RC.. 0602 MO		76,33
SRDC N 2020 K06	20	20	125	12,4	13,0	RC.. 0602 MO		85,04
SRDC N 2525 M06	25	25	150	12,4	15,5	RC.. 0602 MO		87,97
SRDC N 1616 H08	16	16	100	16,4	12,0	RC.. 0803 MO		76,33
SRDC N 2020 K08	20	20	125	16,4	14,0	RC.. 0803 MO		85,04
SRDC N 2525 M08	25	25	150	16,4	16,5	RC.. 0803 MO		87,97
SRDC N 1616 H10	16	16	100	20,3	13,0	RC.. 1003 MO		76,33
SRDC N 2020 K10	20	20	125	20,3	15,0	RC.. 1003 MO		85,04
SRDC N 2525 M10	25	25	150	20,3	17,5	RC.. 1003 MO		87,97

Y7



Key D

2A/28



Combination Key

2A



Clamping screw

2A/28



Solid carbide support R

2A/28




Threaded sleeve

Spare parts

for Article no.

	Article no. 80 950 ... EUR	Article no. 70 950 ... EUR			
70 708 012	7,80	110		2,36	112
70 708 016	7,80	110		2,36	112
70 708 020	7,80	110		2,36	112
70 708 025	7,80	110		2,36	112
70 708 116	7,80	110		2,57	115
70 708 120	7,80	110		2,57	115
70 708 125	7,80	110		2,57	115
70 708 216			8,28	398	3,14 113
70 708 220			8,28	398	3,14 113
70 708 225			8,28	398	3,14 113

MaxiLock-N – PRDC 0° – Toolholder with lever clamping

Neutral
2A/24

Article no.
70 544 ...
EUR


ISO designation	H	B	OAL	LH	WF	torque moment Nm	Insert
	mm	mm	mm	mm	mm		
PRDC N 2525 M12	25	25	150	24	18,5	3	RCMT 1204
PRDC N 3225 P12	32	25	170	24	18,5	3	RCMT 1204
PRDC N 3225 P16	32	25	170	28	20,5	4	RCMT 1606
PRDC N 3225 P20	32	32	170	32	26,0	5	RCMT 2006
PRDC N 4040 S25	40	40	250	42	32,5	6	RCMT 2507

Tool holders with HSK-T interface can be found in → **Chapter 16.**



Spare parts	Article no. 70 950 ...			Article no. 70 950 ...			Article no. 70 950 ...			Article no. 70 950 ...		
	for Article no.	Article no.	EUR	Article no.	EUR	EUR	Article no.	EUR	EUR	Article no.	EUR	EUR
70 544 025	SW2,5	2,45	175	1,76	197	1,22	191	15,52	178	3,19	208	7,09 215
70 544 032	SW2,5	2,45	175	1,76	197	1,22	191	15,52	178	3,19	208	7,09 215
70 544 132	SW3	2,45	176	1,37	196	1,22	192	16,06	387	3,50	390	12,59 384
70 544 23200	SW2	2,45	177	1,12	391	1,22	394	15,23	28100	3,44	28500	17,04 27400
70 544 04000	SW4	2,57	396	1,76	392	1,22	395	18,75	28400	7,48	28600	31,95 27500

MaxiLock-S - SRGC - Toolholder with screw clamping



Illustrations show right-hand versions

ISO designation	H	B	OAL	LH	WF	Insert torque moment Nm	Left-hand 2A/24			Right-hand 2A/24		
	mm	mm	mm	mm	mm		Article no. 70 713 ... EUR	Article no. 70 712 ... EUR	Article no. 70 713 ... EUR	Article no. 70 712 ... EUR		
SRGC R/L 1212 F06	12	12	80	10,0	16	1,2	RC.. 0602 MO	73,60	012	73,60	012	
SRGC R 1616 H06	16	16	100	10,0	20	1,2	RC.. 0602 MO			76,33	016	
SRGC R/L 2020 K06	20	20	125	11,5	25	1,2	RC.. 0602 MO	85,04	020	85,04	020	
SRGC R/L 2525 M06	25	25	150	15,0	32	1,2	RC.. 0602 MO	87,97	025	87,97	025	
SRGC R/L 1616 H08	16	16	100	11,0	20	1,8	RC.. 0803 MO	76,33	116	76,33	116	
SRGC R 2020 K08	20	20	125	13,0	25	1,8	RC.. 0803 MO			85,04	120	
SRGC R/L 2525 M08	25	25	150	16,0	32	1,8	RC.. 0803 MO	87,97	125	87,97	125	
SRGC R/L 1616 H10	16	16	100	12,0	20	3,2	RC.. 1003 MO	76,33	216	76,33	216	
SRGC R/L 2020 K10	20	20	125	13,5	25	3,2	RC.. 1003 MO	85,04	220	85,04	220	
SRGC R/L 2525 M10	25	25	150	17,0	32	3,2	RC.. 1003 MO	87,97	225	87,97	225	



Clamping screw



Solid carbide support R



Threaded sleeve


Spare parts

for Article no.

		Article no. 70 950 ... EUR		Article no. 70 950 ... EUR		Article no. 70 950 ... EUR
70 712 012 / 70 713 012	M2,5x6	2,36	112			
70 712 016	M2,5x6	2,36	112			
70 712 020 / 70 713 020	M2,5x6	2,36	112			
70 712 025 / 70 713 025	M2,5x6	2,36	112			
70 712 116 / 70 713 116	M3x7,3	2,57	115			
70 712 120	M3x7,3	2,57	115			
70 712 125 / 70 713 125	M3x7,3	2,57	115			
70 712 216 / 70 713 216	M3,5x11	3,14	113	12,37	117	M3,5 4,64 171
70 712 220 / 70 713 220	M3,5x11	3,14	113	12,37	117	M3,5 4,64 171
70 712 225 / 70 713 225	M3,5x11	3,14	113	12,37	117	M3,5 4,64 171



Key D



Combination Key

Spare parts

for Article no.

		Article no. 80 950 ... EUR		Article no. 70 950 ... EUR
70 712 012 / 70 713 012	T08	7,80	110	
70 712 016	T08	7,80	110	
70 712 020 / 70 713 020	T08	7,80	110	
70 712 025 / 70 713 025	T08	7,80	110	
70 712 116 / 70 713 116	T08	7,80	110	
70 712 120	T08	7,80	110	
70 712 125 / 70 713 125	T08	7,80	110	
70 712 216 / 70 713 216	T15/SW	8,28	398	
70 712 220 / 70 713 220	T15/SW	8,28	398	
70 712 225 / 70 713 225	T15/SW	8,28	398	